EcoTank ET-14100



PRODUCT SPECIFICATIONS

TECHNOLOGY	
Printing Method	4-colour inkjet printer
Nozzle Configuration	400 Nozzles Black, 128 Nozzles per Color
Minimum Droplet Size	3.3 pl
Ink Technology	Dye Ink
Printing Resolution	4,800 x 1,200 DPI
Category	Photo
All-in-One Functions	Print
PRINT	
Number of colours	4 colour
Printing Speed ISO/IEC 2473	4 15 pages/min Monochrome, 8 pages/min Colour
Maximum Printing Speed	30 pages/min Monochrome (plain paper 75 g/m ²), 20 pages/min Colour (plain paper 75 g/m ²)
First Page Out	Monochrome 8 Seconds, Colour 12 Seconds, According to IEEE/ISO 17629
Colours	Black [Dye], Cyan [Dye], Yellow [Dye], Magenta [Dye]
For detailed information on p	rinting speeds please visit http://www.epson.eu/testing.
PAPER / MEDIA HANDLING	
Paper Formats	A3 (29.7x42.0 cm), A4 (21.0x29.7 cm), A5 (14.8x21.0 cm), A6 (10.5x14.8 cm), B6, B5, B4, Letter,
	Legal, No. 10 (Envelope), DL (Envelope), C6 (Envelope), C4 (Envelope)
Output Tray Capacity	100 Sheets
Paper Tray Capacity	100 Sheets Standard
O	64 g/m² - 300 g/m²
Compatible Paper Weight	64 g/m² - 300 g/m²
General	64 g/m ² - 300 g/m ²
	0.8 Watt (sleep mode), 16 Watt (Printing), 4.2 Watt (Ready), 0.2 Watt (Power off), TEC 0.16 kWh/week
GENERAL	0.8 Watt (sleep mode), 16 Watt (Printing), 4.2 Watt (Ready), 0.2 Watt (Power off), TEC 0.16
GENERAL Energy Use	0.8 Watt (sleep mode), 16 Watt (Printing), 4.2 Watt (Ready), 0.2 Watt (Power off), TEC 0.16 kWh/week
GENERAL Energy Use Supply Voltage	0.8 Watt (sleep mode), 16 Watt (Printing), 4.2 Watt (Ready), 0.2 Watt (Power off), TEC 0.16 kWh/week AC 100 V - 240 V, 50 Hz - 60 Hz
GENERAL Energy Use Supply Voltage Product dimensions	0.8 Watt (sleep mode), 16 Watt (Printing), 4.2 Watt (Ready), 0.2 Watt (Power off), TEC 0.16 kWh/week AC 100 V - 240 V, 50 Hz - 60 Hz 498 x 358 x 165 mm (Width x Depth x Height)
GENERAL Energy Use Supply Voltage Product dimensions Product weight	0.8 Watt (sleep mode), 16 Watt (Printing), 4.2 Watt (Ready), 0.2 Watt (Power off), TEC 0.16 kWh/week AC 100 V - 240 V, 50 Hz - 60 Hz 498 x 358 x 165 mm (Width x Depth x Height) 6.4 kg
GENERAL Energy Use Supply Voltage Product dimensions Product weight Compatible Operating	0.8 Watt (sleep mode), 16 Watt (Printing), 4.2 Watt (Ready), 0.2 Watt (Power off), TEC 0.16 kWh/week AC 100 V - 240 V, 50 Hz - 60 Hz 498 x 358 x 165 mm (Width x Depth x Height) 6.4 kg Mac OS X 10.9.5 or later, Windows 10 (32/64 bit), Windows 11, Windows 7 (32/64 bit),
GENERAL Energy Use Supply Voltage Product dimensions Product weight Compatible Operating	0.8 Watt (sleep mode), 16 Watt (Printing), 4.2 Watt (Ready), 0.2 Watt (Power off), TEC 0.16 kWh/week AC 100 V - 240 V, 50 Hz - 60 Hz 498 x 358 x 165 mm (Width x Depth x Height) 6.4 kg Mac OS X 10.9.5 or later, Windows 10 (32/64 bit), Windows 11, Windows 7 (32/64 bit), Windows 8 (32/64 bit), Windows Server 2008 R2, Windows Server 2012 R2, Windows Server
GENERAL Energy Use Supply Voltage Product dimensions Product weight Compatible Operating	0.8 Watt (sleep mode), 16 Watt (Printing), 4.2 Watt (Ready), 0.2 Watt (Power off), TEC 0.16 kWh/week AC 100 V - 240 V, 50 Hz - 60 Hz 498 x 358 x 165 mm (Width x Depth x Height) 6.4 kg Mac OS X 10.9.5 or later, Windows 10 (32/64 bit), Windows 11, Windows 7 (32/64 bit), Windows 8 (32/64 bit), Windows Server 2008 R2, Windows Server 2012 R2, Windows Server 2016, Windows Vista (32/64 bit), Windows XP Professional x64 Edition SP2 or later, Windows
GENERAL Energy Use Supply Voltage Product dimensions Product weight Compatible Operating Systems	0.8 Watt (sleep mode), 16 Watt (Printing), 4.2 Watt (Ready), 0.2 Watt (Power off), TEC 0.16 kWh/week AC 100 V - 240 V, 50 Hz - 60 Hz 498 x 358 x 165 mm (Width x Depth x Height) 6.4 kg Mac OS X 10.9.5 or later, Windows 10 (32/64 bit), Windows 11, Windows 7 (32/64 bit), Windows 8 (32/64 bit), Windows Server 2008 R2, Windows Server 2012 R2, Windows Server 2016, Windows Vista (32/64 bit), Windows XP Professional x64 Edition SP2 or later, Windows XP SP3 or later (32-bit), Windows Server 2003 R2, Windows Server 2003 SP2 or later
GENERAL Energy Use Supply Voltage Product dimensions Product weight Compatible Operating Systems	0.8 Watt (sleep mode), 16 Watt (Printing), 4.2 Watt (Ready), 0.2 Watt (Power off), TEC 0.16 kWh/week AC 100 V - 240 V, 50 Hz - 60 Hz 498 x 358 x 165 mm (Width x Depth x Height) 6.4 kg Mac OS X 10.9.5 or later, Windows 10 (32/64 bit), Windows 11, Windows 7 (32/64 bit), Windows 8 (32/64 bit), Windows Server 2008 R2, Windows Server 2012 R2, Windows Server 2016, Windows Vista (32/64 bit), Windows XP Professional x64 Edition SP2 or later, Windows XP SP3 or later (32-bit), Windows Server 2003 R2, Windows Server 2003 SP2 or later USB, WiFi, Wi-Fi Direct
GENERAL Energy Use Supply Voltage Product dimensions Product weight Compatible Operating Systems Interfaces WLAN Security	0.8 Watt (sleep mode), 16 Watt (Printing), 4.2 Watt (Ready), 0.2 Watt (Power off), TEC 0.16 kWh/week AC 100 V - 240 V, 50 Hz - 60 Hz 498 x 358 x 165 mm (Width x Depth x Height) 6.4 kg Mac OS X 10.9.5 or later, Windows 10 (32/64 bit), Windows 11, Windows 7 (32/64 bit), Windows 8 (32/64 bit), Windows Server 2008 R2, Windows Server 2012 R2, Windows Server 2016, Windows Vista (32/64 bit), Windows XP Professional x64 Edition SP2 or later, Windows XP SP3 or later (32-bit), Windows Server 2003 R2, Windows Server 2003 SP2 or later USB, WiFi, Wi-Fi Direct WEP 64 Bit, WEP 128 Bit, WPA PSK (TKIP), WPA2 PSK (AES), WPA3-SAE(AES)
GENERAL Energy Use Supply Voltage Product dimensions Product weight Compatible Operating Systems Interfaces WLAN Security Mobile and Cloud printing	0.8 Watt (sleep mode), 16 Watt (Printing), 4.2 Watt (Ready), 0.2 Watt (Power off), TEC 0.16 kWh/week AC 100 V - 240 V, 50 Hz - 60 Hz 498 x 358 x 165 mm (Width x Depth x Height) 6.4 kg Mac OS X 10.9.5 or later, Windows 10 (32/64 bit), Windows 11, Windows 7 (32/64 bit), Windows 8 (32/64 bit), Windows Server 2008 R2, Windows Server 2012 R2, Windows Server 2016, Windows Vista (32/64 bit), Windows XP Professional x64 Edition SP2 or later, Windows XP SP3 or later (32-bit), Windows Server 2003 R2, Windows Server 2003 SP2 or later USB, WiFi, Wi-Fi Direct WEP 64 Bit, WEP 128 Bit, WPA PSK (TKIP), WPA2 PSK (AES), WPA3-SAE(AES)
GENERAL Energy Use Supply Voltage Product dimensions Product weight Compatible Operating Systems Interfaces WLAN Security Mobile and Cloud printing services	0.8 Watt (sleep mode), 16 Watt (Printing), 4.2 Watt (Ready), 0.2 Watt (Power off), TEC 0.16 kWh/week AC 100 V - 240 V, 50 Hz - 60 Hz 498 x 358 x 165 mm (Width x Depth x Height) 6.4 kg Mac OS X 10.9.5 or later, Windows 10 (32/64 bit), Windows 11, Windows 7 (32/64 bit), Windows 8 (32/64 bit), Windows Server 2008 R2, Windows Server 2012 R2, Windows Server 2016, Windows Vista (32/64 bit), Windows XP Professional x64 Edition SP2 or later, Windows XP SP3 or later (32-bit), Windows Server 2003 R2, Windows Server 2003 SP2 or later USB, WiFi, Wi-Fi Direct WEP 64 Bit, WEP 128 Bit, WPA PSK (TKIP), WPA2 PSK (AES), WPA3-SAE(AES) Epson Smart Panel App, Epson Connect (Email Print, Remote Print Driver)
GENERAL Energy Use Supply Voltage Product dimensions Product weight Compatible Operating Systems Interfaces WLAN Security Mobile and Cloud printing services Colour	0.8 Watt (sleep mode), 16 Watt (Printing), 4.2 Watt (Ready), 0.2 Watt (Power off), TEC 0.16 kWh/week AC 100 V - 240 V, 50 Hz - 60 Hz 498 x 358 x 165 mm (Width x Depth x Height) 6.4 kg Mac OS X 10.9.5 or later, Windows 10 (32/64 bit), Windows 11, Windows 7 (32/64 bit), Windows 8 (32/64 bit), Windows Server 2008 R2, Windows Server 2012 R2, Windows Server 2016, Windows Vista (32/64 bit), Windows XP Professional x64 Edition SP2 or later, Windows XP SP3 or later (32-bit), Windows Server 2003 R2, Windows Server 2003 SP2 or later USB, WiFi, Wi-Fi Direct WEP 64 Bit, WEP 128 Bit, WPA PSK (TKIP), WPA2 PSK (AES), WPA3-SAE(AES) Epson Smart Panel App, Epson Connect (Email Print, Remote Print Driver)

LOGISTICS INFORMATION

SKU	C11CK39401BY
EAN code	8715946703022
Country of Origin	Philippines



For more information please contact: Home users: 0343 90 37766 Business users*: 0871 42 37766 Republic of Ireland: 01 436 7742 Or visit us at https://www.epson.co.uk/contactus * 10p per minute plus network extras.

Web: www.epson.co.uk www.epson.ie


Trademarks and registered trademarks are the property of Seiko Epson Corporation or their respective owners. Product information is subject to change without prior notice. Last extracted: 2023-09-28

EcoTank ET-14100

WHAT'S IN THE BOX

- Quick Setup Guide
- Warranty Documents
- Power cable
- 4 x 65ml individual ink bottles (Bk,C,Y,M)
 + 1 extra black ink bottle

INK BOTTLE COMPATIBILITY



1. Quoted ink bottle photo yields are extrapolated based on the ISO/IEC 29103 pattern with Epson's methodology printing photos in 10x15cm format, and NOT based on ISO/IEC 29102. Quoted yields may vary depending on the images that you are printing, the paper type that you are using, the frequency of your prints and environmental conditions such as temperature. During the initial printer setup, a certain amount of ink is used to fill the print head's nozzles, therefore the yield of the initial bundled set can be lower. For more information visit www.epson.eu/pageyield 2. Terms and conditions apply. For details, visit

www.epson.eu/printerwarranty 3. Mobile printing solutions require a wireless and/or an

 Mobile printing solutions require a wireless and/or an internet connection to the printer. For a list of Epson Connect enabled printers, compatible devices, apps and ways to connect, visit www.epson.eu/connect
 For test conditions, please visit www.epson.eu/testing

